



HM-B-DG1-1006 – hyMesh™ Backhaul with 1 Directional Grid Antenna

Description:


- A high performance hyMesh™ product with one grid antenna,
- Designed for a reliable and fast data connection when it matters most.
- Provides a focused high speed data link between critical sites.

Application:

- May be used from an ISP hub site to the client location to provide improved coverage to areas with less than ideal internet service.
- May be used as part of a dedicated data connection between two critical locations within a site.
- Grid is more focused than the Yagi allowing for longer distance, fewer hops, and a higher data through rate.
-



4.5 km Single Grid to Single Grid



Backhaul Grid to Backhaul Grid Coverage



Installation Considerations:

- Used for the initial or end link for an ISP connection with the initial or final data connection provided through Ethernet to the PoE adapter.
- Can also be directly connected through Ethernet to a parallel backhaul or a Data Pipeline Air Grid for higher performance or longer distance connections. Connectivity of over 2km per antenna.

Specifications:

hyMesh™ Firmware	4.8.1 (June 8 2016)
Networking interface	1 x 10/100 BASE-TX (Cat. 5, RJ-45) Ethernet
Wireless Approvals	FCC Part 15.247, IC RS210, CE
Dimensions	Backhaul, no antenna: 13.5"x1.6" / 340mm x 40mm Antenna, each: 11.8"x15.8"x10.5" / 300mm x 400mm x 270mm
Weight	3.3lb / 1.5kg
Enclosure	Aluminum
Operating Frequency	5745MHz-5825MHz
Power Method	Passive PoE (Pairs 4, 5+; 7, 8 Return)
Power Supply	15V 12W PoE Adapter Included
Avg Power Consumption	3W
Antenna Gain	22dBi
Antenna Polarization	Vertical or horizontal
Antenna Frequency	4900MHz - 5850MHz
Vertical / Horizontal Beamwidth	12° / 10°
VSWR	<1.5

22dBi Grid Antenna Gain Pattern

